

Style S Sight Flow Indicator

This sight flow indicator is ideal for you to visually check the flow, presence, colour and condition of a liquid.

- ◆ Screwed and flanged connections
- ◆ Highly visible PTFE spinner
- ◆ CE marked and fully PED compliant
- ◆ High temperature and pressure ratings
- ◆ Short lead times
- ◆ Designed and manufactured in the UK



Application

With the highly visible PTFE spinner the style S sight flow indicator is used to check the flow of a liquid in a pipeline. It can be used in vertical or horizontal lines and is ideal for flow monitoring in full pipes.

Construction

The standard bodies are cast in either carbon steel or 316 stainless steel, though we can produce them in other materials.

The glass windows are held in place by stainless steel covers and screws, and sealed with PTFE gaskets, giving superior protection. For ease of maintenance the glasses can be individually removed and replaced.

For standard applications the indicator is fitted with toughened soda lime glass discs to BS3463 and rated to 16 bar. For steam and condensate we recommend toughened borosilicate glass, while for alkaline liquids mica discs can be used to protect the glass.

The sight glasses can be supplied with screwed connections to NPT, BSP parallel or taper. The standard flanges available are ANSI 150, ANSI 300 and PN16, though other flanges can be supplied.

Options

Body - Primary Flowpoints stock carbon and stainless steel, but can supply sight glasses in special materials such as super duplex, hastelloy or low carbon steels.

Glass - High pressure toughened soda lime to BS3463 rated to 40 bar or 60 bar depending on the size, toughened borosilicate to BS3463 or DIN7080 rated up to 16 bar. Higher pressures are achievable by reducing the viewing diameter. The high pressure range uses powder coated mild steel covers as standard. Stainless steel covers are available as an option.

Gaskets - Graphite gaskets are available if required.

Fasteners - We can also offer A4 stainless steel fasteners when necessary.

Quality

All Flowpoints indicators are manufactured to the highest standards.

The quality system is independently audited by BSI and certified to ISO 9001. The indicators are fully PED compliant and CE marked where required. TUV are our external auditors for the Pressure Equipment Directive.

Full material traceability is maintained, material certificates and pressure test certificates are supplied on request.

Specification Code

Code


Description

SS				Stainless steel body BS 1504 316 C16
CS				Carbon steel body BS 1504 162 GR480
				Glass Material & Pressure Range
H				Toughened soda lime glass to BS3463 rated to 16 bar (standard)
B				Toughened soda lime glass to BS3463 rated to 40 bar
HB				Toughened borosilicate glass to BS3463 rated to 6 bar
				Toughened borosilicate glass to DIN 7080 rated to 16 bar
				Indicator Size
				Minimum Flow Rate - Lit / Min
	008			8mm / 1/4" (screwed only) 2.0
	010			10mm / 3/8" (screwed only) 2.0
	015			15mm / 1/2" 3.5
	020			20mm / 3/4" 4.2
	025			25mm / 1" 7.0
	040			40mm / 1 1/2" 17.0
	050			50mm / 2" 25.0
	080			80mm / 3" 60.0
	100			100mm / 4" 100.0
	150			150mm / 6" 250.0
	200			200mm / 8" 500.0
				End Connection
	A			ANSI 150
	C			ANSI 300
	N			PN16
	1			BSP
	2			BSPT
	3			NPT
	4			Socket Weld

Materials of Construction

- Covers - Stainless steel ASTM A351 CF8M (316)
- Powder coated mild steel grade S355J2+N
- Internal Gasket - PTFE
- External Gasket - Klingersil C4400
- Edge Protector - Klingersil C4400
- Fasteners (Standard) - A2 Stainless steel
- (High Pressure) - High tensile steel
- Spinner - Glass filled PTFE

Dimensions



NOMINAL BORE	LENGTH L1	LENGTH L2	WIDTH W	DEPTH D	CLEARVIEW C
8/10mm(screwed)	85	N/A	63	60	42
15/20mm	85	130	63	60	42
25mm	95	140	72	66	48
40mm	120	180	102	84	62
50mm	150	220	118	106	77
80mm	NA	260	160	170	100
100mm	NA	260	196	170	100
150mm	NA	360	304	220	150
200mm	N/A	460	370	280	200